

Commercial Solutions

Product Specifications

Collection Name	Elevation	
Style Number	52900	
Product Type	Broadloom	
Surface Texture	Graphic level loop	
Pile Fibre Content	100% BCF anti-static Colorloc Nylon	
Dye System	Solution Dyed	
Primary Backing	Woven Polypropylene	
Secondary Backing	Woven synthetic backing	
	Imperial	Metric
Pile Weight	30.0 oz / s.y.	1017 g/m2
Gauge	1/10 ga	39.4 / 10 cm
Stitches	12.0 / in.	47.0 / 10 cm
Pile Height	.196 in.	5.0 mm
Pile Thickness	.159 in.	4.0 mm
Density Factor	6792	10,0 ktex
Total Weight	71.24 oz/s.y.	2415 g/m2
Pattern Repeat	W 7/8 in. X L 7/16 in.	W 0.9 cm x L 1.1 cm
Width	12 ft	366 cm

Performance Specifications

Flammability	Meets ASTM E-648 test standards Radiant Panel Class I
Somke Density	Meets ASTM E-662 test standards <450 Flaming mode
Anti-Static Properties	Less than 3.0 kv at 20% R.H.. & 21° C
Lightfastness	L7 or Better
Resistance to Wet Cleaning	Grey Scale 5
Tuft Bind	Tuftloc Backing System 15 lbs / 67 N
Treatment	Steriseptic Antimicrobial Treatment

Warranty Information

- Venture Lifetime Warranty Wear
- Venture Lifetime Warranty Anti-static
- Venture Lifetime Warranty No-Zippering
- Venture Lifetime Warranty Colorfast to Light
- Venture Lifetime Warranty Colorfastness to Atmospheric Contaminants

Environmental

Indoor air quality no. GLP 7492

Venture Carpets Inc. reserves the right to modify the specification to improve this product without prior notice and without prejudice