

PLATEAU

by INTERFLOR

TECHNICAL DATA SHEET

Manufactured in accordance with ANSI A 137.1 standards.

MATTE PORCELAIN FLOOR TILE

TECHNICAL SPECIFICATIONS				
V Rating (Variation)	Coefficient of Friction (COF)	Porcelain Enamel Institute (P.E.I.)	Water Absorption (ISO 10545-3)	Breaking Strength (ISO 10545-4)
V2 - Slight Variation	> 0.60 Wet	4 - Moderate to heavy traffic	1.5%	1448
Impact Resistance (ISO 10545-5)	Abration Resistance (ISO 10545-7)	Thermal Shock Resistance (ISO 10545-9)	Moisture Expansion (ISO 10545-10)	Crazing Resistance (ISO 10545-11)
0.88	Class 3 - 1500	Pass	0.02mm	Pass
Frost Resistance (ISO 10545-12)	Resistance to Chemicals (ISO 10545-13)	Resistance to Staining (ISO 10545-14)	Slip Resistance (DIN 51130)	Hardness of Surface *Mohs (EN15771)
Pass	Pass	Class 5 - Pass	8.2° - R9	5

PACKAGING DETAILS				
Tile Size	Thickness	Weight per Carton (KGS)	Tiles per Carton	SQFT per Piece
300 x 600mm	9.4mm	29.5	8	2