


Caratteristiche Tecniche • Technical Features • Technische Eigenschaften*

Gres porcellanato smaltato impasto colorato - Glazed through body porcelain stoneware - Glasiertes Durchgefaerbtes Feinsteinzeug

| | NORME TEST N° | DESCRIZIONE DESCRIPTION | VALORE A NORMA REQUIRED STANDARD | VALORE - MATT RESULTS - MATT | VALORE - LEV RESULTS - LEV |
|--|---|--|----------------------------------|--|--|
| | ISO 10545/3 | ASSORBIMENTO D'ACQUA - WATER ABSORPTION ABSORPTION D'EAU - WASSERAUFNAHME | ≤ 0,5% | CONFORME CONFORMS | CONFORME CONFORMS |
| | ISO 10545/4 | RESISTENZA ALLA FLESSIONE - BENDING STRENGTH RESISTANCE A LA FLEXION - BIEGESTÄRKE | R ≥ 35 N/mm ² | CONFORME CONFORMS | CONFORME CONFORMS |
| | ISO 10545/8 | COEFFICIENTE DI DILATAZIONE TERMICA LINEARE THERMAL EXPANSION COEFF. BETWEEN 20°C - 100°C COEFF. DE DILATATION THERMIQUE LINEAIRE ENTRE 20°C ET 100°C WÄRMEAUSSDEHNUNG ZWISCHEN 20°C UND 100°C | < 10 ⁻⁴ | 9x10-5x0-1 | 9x10-5x0-1 |
| | ISO 10545/9 | RESISTENZA AGLI SBALZI TERMICI - RESISTANCE TO THERMAL SHOCK RESISTANCE AUX CHOC'S THERMIQUES TEMPERATURWECHSELBESTÄNDIGKEIT | | RESISTE - RESISTANT RESISTE - BESTÄNDIG | RESISTE - RESISTANT RESISTE - BESTÄNDIG |
| | ISO 10545/11 | RESISTENZA AL CAVILLO - CRAZING RESISTANCE RESISTANCE AU TRASSAILLAGE - HAARRISSFESTIGKEIT | | RESISTE - RESISTANT RESISTE - BESTÄNDIG | RESISTE - RESISTANT RESISTE - BESTÄNDIG |
| | ISO 10545/14 | RESISTENZA ALLE MACCHIE - STAIN RESISTANCE RESISTANCE AUX TACHES - FLECKENFESTIGKEIT | min. Classe 3 | CONFORME CONFORMS | CONFORME CONFORMS |
| | ISO 10545/13 | RESISTENZA ALL'ATTACCO CHIMICO - CHEMICAL RESISTANCE RESISTANCE A L'ATTACQUE CHIMIQUE - FÄHIG GEGEN SÄUREN UND LAUGEN | min. 8 | CONFORME CONFORMS | CONFORME CONFORMS |
| | ISO 10545/2 | LUNGHEZZA E LARGHEZZA - LENGTH AND WIDTH LONGUEUR ET LARGEUR - LÄNGE UND BREITE | ± 0,5% | CONFORME CONFORMS | CONFORME CONFORMS |
| | ISO 10545/2 | SPESORE - THICKNESS ÉPAISSEUR - STÄRKE | ± 5% | CONFORME CONFORMS | CONFORME CONFORMS |
| | ISO 10545/2 | ORTOGONALITÀ - WEDGING ORTHOGONALITÉ - RECHTWINKLICHKEIT | ± 0,5% | CONFORME CONFORMS | CONFORME CONFORMS |
| | ISO 10545/2 | PLANARITÀ - WARPAGE PLANÉITÉ - EBENFLÄCHIGKEIT | ± 0,5% | CONFORME CONFORMS | CONFORME CONFORMS |
| | ISO 10545/12 | RESISTENZA AL GELO - FROST RESISTANCE RESISTANCE AU GEL - FROSTBESTÄNDIGKEIT | | RESISTE - RESISTANT RESISTE - BESTÄNDIG | RESISTE - RESISTANT RESISTE - BESTÄNDIG |
| | ISO 10545/7 | RESISTENZA ALL'ABRASIONE PROFONDA - DEEP ABRASION RESISTANCE RESISTANCE A L'ABRASION PROFONDE - TIEFENWERSCHLEISSBESTÄNDIGKEIT | | BIANCO: IV GRIGIO: IV BLU: IV NERO: III | BIANCO: IV GRIGIO: IV BLU: III NERO: II |
| | BOT 3000 WET DCOF DIN 51130 R | RESISTENZA ALLO SCIVOLAMENTO SLIP RESISTANCE - RESISTANCE AU GLISSEMENT BESTIMMUNG DER RUTSCHEMME EIGENSCHAFT water, oil, grease, etc. create slippery conditions. floor applications with exposure to these conditions require extra caution in product selection. | ≥ 0,42 | Tile 1: 0,60 Tile 2: 0,61 Tile 3: 0,60 | RS |



SOLUZIONI DI POSA
cm 30x60 - 12"x24"
cm 60x120 - 24"x48"

Per una corretta realizzazione si consiglia di posare i formati lunghezza 60 cm e 120 cm, sfalsati a correre al massimo 20 cm o posa pari.

INSTALLATION INFORMATION
cm 30x60 - 12"x24"
cm 60x120 - 24"x48"

For 60 cm (24") and 120 cm (48") long tiles, staggering should not exceed 20cm (8").

VERLEGEBEISPIELE
cm 30x60 - 12"x24"
cm 60x120 - 24"x48"

Für einen korrekten und einwandfreien Belag, die Formaten mit 60 cm und 120 cm Länge sollten bei der Verlegung maximal 20 cm versetzt sein.

Noi consigliamo fortemente l'uso di un sistema di posa con distanziatori autolivellanti.

Wir empfehlen dringend die Verwendung von einem Befestigungssystem mit leveling system.

We strongly recommend using a tile edge leveling system during installation.

Il est vivement recommandé l'utilisation d'un système de pose avec des croisillons autivelant.

SHADE VARIATION



*These test results may change from lot to lot

IMBALLI PACKAGING

UNITÀ DI MISURA
UNIT OF MEASURES



| | | | | | | | | |
|----------------------------|-----------------------------|----------------|----|-------|------|----|-------|---------|
| Aqua Lev. | 60x120 (24"x48") | M ² | 2 | 31,95 | 1,44 | 21 | 30,24 | 670,95 |
| Aqua Rett./Lev. | 60x60 (24"x24") | M ² | 3 | 24,80 | 1,08 | 40 | 43,20 | 992,00 |
| Aqua Rett./Lev. | 30x60 (12"x24") | M ² | 6 | 24,80 | 1,08 | 40 | 43,20 | 992,00 |
| Aqua Rett./Lev. | 30x30 (12"x12") | M ² | 11 | 22,45 | 0,99 | 48 | 47,52 | 1077,60 |
| Aqua Lev. | 7,5x30 (3"x12") | M ² | 17 | 9,03 | 0,38 | 84 | 31,92 | 758,52 |
| Aqua Lev. | 7,5x15 (3"x6") | M ² | 50 | 13,00 | 0,57 | 76 | 43,32 | 988,00 |
| Aqua Hexagon | 29,3x29,4 (11 1/2"x11 1/2") | FOGLIO/SHEET | 8 | 14,50 | - | 42 | - | 609,00 |
| Aqua Freccia | 33,3x37,5 (13 1/8"x14 3/4") | FOGLIO/SHEET | 8 | 14,50 | - | 42 | - | 609,00 |
| Aqua Mosaico 5x5 (2"x2") | 30x30 (12"x12") | FOGLIO/SHEET | 8 | 16,14 | - | 42 | - | 677,88 |
| Aqua Battiscopa Rett./Lev. | 7x60 (2 3/4"x24") | PZ | 15 | 14,00 | - | 40 | - | 560,00 |
| Aqua Battiscopa Rett./Lev. | 7x120 (2 3/4"x48") | PZ | 6 | 13,00 | - | 40 | - | 520,00 |

ceramiche
campogalliano®

info@ceramichecampogalliano.it
www.ceramichecampogalliano.it
tel +39 0536 832393 - fax +39 0536 913591

a brand of **erde 1999**®
ITALIAN CERAMICS

Verde 1999 srl - Via Ghiarola Nuova, 158
41042 Fiorano Modenese, MO Italy
tel +39 0536 832393 - fax +39 0536 913591
www.verde1999.com - info@verde1999.com

Ceramics of Italy

made in Italy
100%