

Commercial Solutions

Product Specifications

| | |
|--------------------|-------------------------------------|
| Style Name | Traffix SDN |
| Style Number | 59200 |
| Product Type | Broadloom |
| Surface Texture | Graphic Level loop |
| Pile Fibre Content | 100% BCF anti-static Colorloc Nylon |
| Dye System | Solution Dyed |
| Primary Backing | Woven Polypropylene |
| Secondary Backing | Woven synthetic backing |

| | <u>Imperial</u> | <u>Metric</u> |
|----------------|------------------------|-----------------------|
| Pile Weight | 28.0 oz / s.y. | 950 g/m ² |
| Gauge | 1/10 ga | 39.4 / 10 cm |
| Stitches | 8.0 / in. | 31.5 / 10 cm |
| Pile Height | .196 in. | 5.0 mm |
| Pile Thickness | .137 in. | 3.5 mm |
| Density Factor | 7357 | 10.9 ktex |
| Total Weight | 68.97 oz/s.y. | 2338 g/m ² |
| Width | 12 ft | 366 cm |

Performance Specifications

| | |
|----------------------------|---|
| Flammability | Meets ASTM E-648 test standards Radiant Panel Class I Meets CGSB standards 4GP-155 & 4GP-129 |
| Smoke Density | Meets ASTM E-662 test standards <450 Flaming mode |
| Anti-Static Properties | Less than 3.0 kv at 20% R.H.. & 21° C |
| Lightfastness | L7 or Better |
| Resistance to Wet Cleaning | Grey Scale 5 |
| Tuft Bind | Tuftloc Plus Backing System No Edge Ravel & Delamination |
| Treatment | Steriseptic Antimicrobial Treatment |

Warranty Information

- Limited Lifetime Warranty Wear
- Limited Lifetime Warranty Anti-staic
- Limited Lifetime Warranty No-Zippering
- Limited Lifetime Warranty Colorfast to Light
- Limited Lifetime Warranty Colorfastness to Atmospheric Contaminants

Environmental

| | |
|------------------------|----------|
| Indoor air quality no. | GLP 7492 |
|------------------------|----------|