

**THE TRANSCEND™ COLLECTION**

Transcend Luxury Floors are constructed for performance with a commercial level 20 mil wear layer, while providing beautiful floor designs and colors. Transcend SureSet is uniquely designed to provide creative room designs that are easy, fast and low cost to install with repositionable plank & tile technology. SureSet is backed by a Lifetime Residential Limited Warranty and a 10-year Commercial Limited Warranty.

**Details**

<b>Nominal Thickness:</b>	.177" (4.5 mm)
<b>Wear Layer Thickness:</b>	20 Mils
<b>Finish Edge:</b>	Microbeveled
<b>ASTM D2047 (slip):</b>	SCOF ≥ 0.6
<b>ASTM E648 (Fire):</b>	>.45 w/cm <sub>2</sub>
<b>ASTM E662 (Smoke):</b>	<450
<b>ASTM F925 (Staining):</b>	Good
<b>ASTM F970 (Static Load Limit):</b>	Passes
<b>ASTM (Heat Stability):</b>	Δ E < 8
<b>ASTM F1515 (Light Stability):</b>	Δ E < 8
<b>ASTM E2179 (Impact Sound Reductions):</b>	Δ IIC 12 dB 57 (Includes SureStart-Underlayment)
<b>Installation System:</b>	Factory applied repositionable adhesive
<b>FloorScore® Certification SCS-EC10.3-2014:</b>	SCS-FS-04372

	6" x 36"	9" x 48"	12" x 24"	12" x 36"
<b>Sq. Ft. per Carton:</b>	24	24	24	24
<b>Planks per Carton:</b>	16	8	12	8
<b>Cartons per Pallet:</b>	45	56	56	45
<b>Lbs. per Carton:</b>	40.7	40.7	40.7	40.7

**Installation**

<b>Use:</b>	Residential, Commercial
<b>Location:</b>	Below, on and above grade concrete, above grade plywood and approved existing floors.

- Maintain the work area, flooring and adhesive between 65° F and 85° F (18°C - 29°C) for 48 hours before, during and after installation.
- Maintain relative humidity between 40% and 70%.
- Cartons shall be stored horizontally at all times.
- To insure the best color match when installing two or more cartons, make sure run numbers on each carton are the same.
- Use only cementitious based patching and leveling compounds.
- Floating Floor when using with PS+3 (**vinyl side-up**) and SureStart underlayments.
- Refer to SureSet Installation Manual for complete and detailed installation instructions.

**Maintenance**

- SureSet can be washed immediately after installation.
- Furniture can be replaced immediately after installation.
- Never slide heavy furniture or appliances across the floor. Place sheets of plywood over floor when moving furniture and appliances into position.
- Maintain post installation temperature between 65° F and 85° F. Maintain relative humidity between 40% and 70%.
- Use non staining mats or area rugs at doorways and entranceways to collect excess water, sand, grit and debris. Clean the mats and area rugs on a regular basis.
- Use smooth, hard plastic or metal furniture rests or glides under frequently moved furniture to avoid scratches and indentations. Do not use felt pads.
- Wash floor with Tarkett SureShine® Floor Cleaner or equal neutral floor cleaner. Dilute floor cleaner accordingly.

**Warranty:**

<b>Lifetime Residential Limited Warranty</b>	<b>10 Year Commercial Limited Warranty</b>
--	--