



# CALACATTA BORGHINI

Porcelain Tile

CENTURA TILE




30 x 60 cm (12" x 24")  
**CALACATTA BORGHINI**



30 x 60 cm (12" x 24")  
**CALACATTA BORGHINI**



33 x 33 cm (13" x 13")  
**CALACATTA BORGHINI**



5 x 5 cm (30 x 30)  
2" x 2" (12" x 12")  
**CALACATTA BORGHINI**  
Mosaics



5 x 5 (2" x 2")  
28 x 33 (11" x 13")  
**CALACATTA BORGHINI**  
Hexagon Mosaics



5x15 (2" x 6")  
28 x 33 (11" x 13")  
**CALACATTA BORGHINI**  
Picket Mosaics

## PACKING INFORMATION

PRODUCT	THICKNESS	Pcs x Box	Sqm x Box	Sqft x Box	Kgs x Box	Lbs x Box	Box x Pal	Sqm x Pal	Sqft x Pal	Kgs x Pal	Lbs x Pal
30 x 60 (12" x 24") CALACATTA BORGHINI	8,0 mm.-0,32"	9	1,62	17,43	28,1	61,9	32	51,84	558,00	933	2028
33 x 33 (13" x 13") CALACATTA BORGHINI	7,8 mm.-0,31"	13	1,42	15,28	23,5	51,6	46	65,32	703,00	1100	2425
5 x 5 (2" x 2") - 28 x 33 (11" x 13") CALACATTA BORGHINI HEXAGON MOSAICS	8,0 mm.-0,32"	5	0,40	4,30	7,20	15	90	36,00	387,50	685	1510
5 x 15 (2" x 6") - 28 x 33 (11" x 13") CALACATTA BORGHINI PICKET MOSAICS	8,0 mm.-0,32"	5	0,39	4,20	7,10	15	90	35,10	377,80	675	1488
5x5 (2"x2") - 30X30 (12"X12") CALACATTA BORGHINI MOSAICS	8,0 mm.-0,32"	10	0,88	9,47	18	39,68	48	42,34	455,74	894	1971

## GENERAL SPECIFICATIONS

		Appendix G Group BlaSerie: <b>CALACATTA BORGHINI</b> Porcelain tiles Appendix G Group Bia			MONTECERA AVERAGE VALUE
TECHNICAL FEATURES	NORMS	Requirement for Nominal Size N.			CALACATTA BORGHINI
		7 cm ≤ N < 15 cm	N ≥ 15 cm		Matt
LENGTH AND WIDTH	EN ISO 10545-2	±0,9mm.	± 0,6%	±2,0mm	Confirmed
THICKNESS	EN ISO 10545-2	±0,5mm.	± 0,5%		Confirmed
STRAIGHTNESS	EN ISO 10545-2	±0,75mm.	± 0,5%	±1,5mm	Confirmed
SQUARNESS	EN ISO 10545-2	±0,75mm.	± 0,6%	±2,0mm	Confirmed
SURFACE FLATNESS	EN ISO 10545-2	±0,75mm.	± 0,5%	±2,0mm	Confirmed
WATER ABSORPTION	EN ISO 10545-3	≤ 0,5%			≤ 0,5%
BREAKING STRENGTH	EN ISO 10545-4	1300 N			1400 N
MODULUS OF RUPTURE	EN ISO 10545-4	≥35 N/mm <sup>2</sup>			≥ 40 N/mm <sup>2</sup>
THERMAL SHOCK RESISTANCE	EN ISO 10545-9	Required			Resistant
FROST RESISTANCE	EN ISO 10545-12	Required			Resistant
CHEMICAL RESISTANCE	EN ISO 10545-13	Indicated by manufacturer			Resistant
RESISTANCE TO STAINS	EN ISO 10545-14	Indicated by manufacturer			Resistant
DCOF (Wet)	ANSI B 101.3	Indicated by manufacturer			> 0,42
SCRATCH HARDNESS (MOHS)		Indicated by manufacturer			Min. 6
ABRASION RESISTANCE (PEI)	EN ISO 10545-7	Indicated by manufacturer			4
SHADE VARIATION		Indicated by manufacturer			V3